



Item No: WX2021N

2-Channel Soldering Station, 200 W
(255 W)

KEY FEATURES

- + High Powered Digital Soldering Stations WX 2
- + Capacitive glass touch screen is chemical and temperature resistant
- + Turn and click wheel with enter key and finger guide is intuitive to use
- + Multi-language menu navigation
- + Large graphic LCD display can be viewed from all angles
- + Acts as a benchtop controller for the WHP1000 / WHP3000 hot plates
- + Acts as a benchtop controller for the Zero Smog 4V / 6V Filtration units
- + Multi-purpose USB port for parameter configuration and data logging
- + Compatible with all WX series soldering pencils

TECHNICAL DATA

| | |
|-------------------------------------|--|
| Dimensions L x W x H | 6.8 x 6.0 x 5.3 in |
| Equipotential Bonding Socket | Via 3.5mm Pawl Socket on Back of Device |
| ESD Safe | Yes |
| Fuse | T2A |
| Interface | 1x USB, 2x RS232, 1x Switching Output |
| Number of Channels | 2 |
| Power | 200 W (255 W) |
| Temperature Accuracy °C | ± 9 °C |
| Temperature Accuracy °F | ± 17 °F |
| Temperature Range (Depends on Tool) | 199 - 998°F |
| Temperature Range °C | 93 - 537 °C |
| Temperature Range °F | 199 - 998 °F |
| Temperature Stability °C | ±2 °C |
| Temperature Stability °F | ±4 °F |
| Tip Type | RT3MS WX |
| UPC | 037103304810 |
| USB | USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types |
| Voltage | 120 V |